

LAVATEC

The LAVATEC range of Tunnels

		Primary Application	Water consumption 3-8ltr/kg	Disinfection of linen guaranteed (3)	Productivity as a result of mechanical action	Double Drum	Ability to process different classifications	Ability to process very different classifications	Bath ratios	Hygienic / Healthcare applications	Modification of waterflow in future	Relative cost per compartment	Full rotation action possible	No. motors / running possible with motor failure?	Heating possible in all compartments	Loading capacity	Number of modules
Classic BT		Hospitality / Healthcare - light to med soiling - counter-flow - low water usage	very low	✓	good	80-100%	med	low	1/36	good	✓	£	✗	(4) 4 / yes	✓	25-100 kg	8-20
Classic CT		Hospitality / Healthcare / Restaurant - med-heavy soiling - counterflow	low	✓	very good	100%	very good	good	1/51	good	✓	££	✓	4 / yes	✓	35-60 kg	8-20
Ecoclean BT		Hospitality / Healthcare - light - heavy soiling - incompatible linen without excessive water use - standing bath	very low	✓ ⁽¹⁾	good	30-60%	very good	good	1/36	med	(2)	£	✗	(4) 4 / yes	✗	25-100 kg	8-20
Ecoclean CT		Hospitality / Healthcare - med to very heavy soiling - incompatible linen without excessive water use - standing bath	very low	✓ ⁽¹⁾	very good	30-60%	very good	good	1/51	med	(2)	£	✓	4 / yes	✗	35-60 kg	8-20
Bioclean BT		Hospitality / Healthcare light to heavy soil compatible colours	very low	✓✓	good	100%	very good	good	1/36	very good	✓	££	✗	(4) 4 / yes	✓	25-100 kg	8-20
Classic Virtual tunnel BT (mini tunnel)		Hospitality / Healthcare / restaurant med soil Virtually double the No compartments	(7) low	✓	good	100%	very good	very good	1/36	very good	✓	£££	✗	(4) 4 / yes	✓	25-100 kg	4-7
Classic Virtual tunnel CT (mini tunnel)		Hospitality / Healthcare / restaurant heavy soil Virtually double the No compartments	(7) low	✓	very good	100%	very good	very good	1/51	very good	✓	£££	✓	(4) 4 / yes	✓	35-60 kg	4-7
Ecoclean G-PRO BT		Industrial / food / coloured garments standing bath, no mixing of water, 4 x recovery tanks	(6) low	✓	good	40-70%	very very good	very very good	1/36	✗	(2)	£££	✗	4 / yes	✗	25-100 kg	8-20
Ecoclean G-PRO CT		Industrial / food / coloured garments standing bath, no mixing of water, 4 x recovery tanks	(6) low	✓	very good	40-70%	very very good	very very good	1/51	✗	(2)	£££	✓	4 / yes	✗	35-60 kg	8-20

(0) : Some of these tunnels, with additional options can be used in another application other than the one specified here

(1) : Except in an extended shutdown of the tunnel - it is not possible to heat the wash zone

(2) : The single skin compartments cannot be changed

(3) : Control ensures the disinfection time and temperature are correct - the linen can not leave the wash zone before receiving 100% of its disinfection time without dropping below the temperature setpoint

(4) : If more than 5 modules

(5) : In normal use. The tunnel is equipped with level control and / or metered water in jection to ensure good transfer + tunnel always checks the load is correctly loaded in the first module

(6) : Low power consumption for this class of article mixed together on the same tunnel (clothing industry, food processing, ...)

(7) : depends on the number of bath change as a function of mix Article

LAVATEC